



US008056147B1

(12) **United States Patent**  
**Patel**

(10) **Patent No.:** **US 8,056,147 B1**

(45) **Date of Patent:** **Nov. 15, 2011**

(54) **NECKTIE HAVING FASTENING SYSTEM FOR SECURING NECKTIE TO SHIRT BUTTON**

(76) Inventor: **Girish K. Patel**, Sunset Beach, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 194 days.

(21) Appl. No.: **12/541,964**

(22) Filed: **Aug. 16, 2009**

(51) **Int. Cl.**  
**A41D 25/04** (2006.01)

(52) **U.S. Cl.** ..... **2/145**

(58) **Field of Classification Search** ..... 2/144, 145, 2/149; 24/54, 55, 66.1, 66.2

See application file for complete search history.

2,893,086 A	7/1959	Parker	
2,946,106 A	7/1960	Moran, Jr.	
3,151,371 A	10/1964	Ellestad	
3,453,696 A	7/1969	Mates	
3,487,471 A	1/1970	Hagen	
3,494,003 A	2/1970	Bower, Jr.	
3,827,108 A	8/1974	Jewett	
4,554,710 A	11/1985	Grant	
4,827,536 A	5/1989	Sung	
4,827,576 A	5/1989	Prince, Jr.	
4,920,579 A	5/1990	Swain	
4,972,523 A *	11/1990	Begg .....	2/145
5,007,139 A	4/1991	Ahern	
5,095,546 A	3/1992	Jones	
5,109,547 A	5/1992	Abdallah	
5,165,112 A	11/1992	Dawes	
5,235,730 A	8/1993	Townsend	
5,239,707 A	8/1993	Pileggi	
5,315,713 A	5/1994	Pileggi	
5,353,438 A	10/1994	Voiles	
5,715,538 A	2/1998	Soll	

(Continued)

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,056,609 A	3/1913	Walton
1,291,090 A	1/1919	Nuzum
1,647,407 A	11/1927	Hostetter
1,707,591 A	4/1929	Young
1,764,705 A	6/1930	Ward
1,798,432 A	3/1931	Ratajack
1,897,734 A	2/1933	Rossner
2,068,454 A	1/1937	Helske
2,100,870 A	11/1937	Petrie et al.
2,195,594 A	4/1940	Kreisler
2,275,682 A	3/1942	Rantz
2,481,367 A	9/1949	Thompson
2,541,660 A	2/1951	Naftali
2,557,635 A	6/1951	Cregar
2,736,033 A	2/1956	Brunetti et al.
2,738,513 A	3/1956	Carty
2,743,452 A	5/1956	Waterbury
2,746,055 A	5/1956	Gleason
2,749,553 A	6/1956	Miller

*Primary Examiner* — Tejash Patel

(74) *Attorney, Agent, or Firm* — Jerry Turner Sewell

(57) **ABSTRACT**

A necktie has an integrated system to limit movement of the free ends of the necktie when worn. The necktie has a wide end section and a narrow end section. The necktie has a selected width transition from the wide end section to the narrow end section. The overall length of the necktie is selected to allow the necktie to be secured to a person's neck using a selected knot-tying technique such that the wide end of the necktie is positioned at a selected location with respect to the person's waistline and such that the narrow end of the necktie is positioned behind the wide end of the necktie. At least one loop is secured to the back of the wide end of the necktie. The narrow end of the necktie passes through the loop. At least one buttonhole is formed through the narrow end of the necktie.

**8 Claims, 3 Drawing Sheets**

